VICTORY VF40D Forklift

Competitive finance options available



Why rent when you can

Buy For Less!!!

Key Features

- 4000KG Capacity
- 4500mm 3 Stage Container Mast with sideshift
- 65HP Diesel Perkins Type Motor, auto transmission
- Pneumatic tyres (solids available)
- 1220mm tynes
- Adjustable steering column
- Digital dash warning system / Operator Safety system
- Flashing light / Driving and rear lighting included

12 Month / 2000 Hour
Full parts & labour warranty
Australia wide

Purchase price
\$32,900
Incl GST



www.safeliftsolutions.com.au

Safelift Solutions

1 England Street Dandenong South VIC 3175

Sales Mobile: 0410 100 550 Ph: 03 9706 5266

Fax: 03 9706 5266

sales@safeliftsolutions.com.au

Find us on Facebook

VICTORY VF40D Forklift Specifications

MANUFACTURER	VICTORY
Model	VF40D
Power type	Diesel
Rated capacity	4500 kg
Load centre	500 mm
Max. lift height of mast with Load-backrest	4500 mm
Max lift height of fork (standard)	3000 mm
Height of mast (standard)	2150 mm
Free lift height (standard)	150 mm
Height of Load-backrest	1240 mm
Distance from seat to load-backrest	1000 mm
Front wheel overhead	2105 mm
Length with fork	3965/2895 mm
Front overhang	500 mm
Rear overhang	495 mm
Min. ground clearance	130 mm
Overall width	1410 mm
Tread (front /rear)	1160/1065 mm
Min. Turning radius (outside)	2700 mm
Min. Turning radius (inside)	230 mm
Min. Intersecting aisle	2685 mm
Mast tilt angle	6°/12° deg
Fork size	1070X130X50 mm
SPEEDS	
Max Drive speeds (with/without load)	18/19 km/h
Lifting speeds (with load)	350/380 mm/s
Lowering speeds (with /without full load)	350/400 mm/s
May tractive force	20/18 KN

Max Drive speeds (with/without load)	18/19 km/h	
Lifting speeds (with load)	350/380 mm/s	
Lowering speeds (with /without full load)	350/400 mm/s	
Max. tractive force	20/18 KN	
Max grade ability (with/without full load)	15/18 %	
Total weight	5310 kg	
Quantity of wheels	2F x 2R	

TYRES

Type of tyres	Pneumatic Tyres
Front Tyres	250-15-16PR
Rear Tyres	6.50-10-10PR
Driving Brake	hydraumatic pedal
Parking Brake	mechanical manual
Battery	12 / 80 V/AH

ENGINE (Standard)

Model	XINCHANG 4D35G
Rated output	48/2200 kw/rpm
Rated torque	230/1600-1800 N.m/rpm
No of cylinder	4, 98X110
Displacement	3.5 L
Fuel tank capacity	80 L
Number of speeds for transmission	1-1 Power shift transmission

What Makes VICTORY Different?

- Industry Leading Design and Manufacturing
- Machines built for Australian conditions
- Electro-static paint to guard against corrosion / Full Sized cabins
- Excellent Parts & Service Backup Australia wide
- Great Transport Rates Australia Wide

All Our Machines are 100% Backed by a 100% Australian Owned Company